

Crossovers

Crossover halves simply bolt together for assembly. 300lb capacity. Rigid 1" square tubing. 24" wide steps. Steps are 7" deep with a deeper 21", 28" or 35" platform at top. Perforated or Grip Strut tread for slip-resistant footing. Meets OSHA standards.



| # of Steps | Clearance WxH | Overall WxLxH | Weight | EGA # | EGA # |
|------------|------------------|------------------|--------|-------|-------|
| 4 | 22x37 | 29x76x70 | 84 | C001 | C010 |
| 4 | 29x37 | 29x84x70 | 89 | C002 | C011 |
| 4 | 36x37 | 29x91x70 | 96 | C003 | C012 |
| 5 | 22x47 | 29x88x80 | 145 | C004 | C013 |
| 5 | 29x47 | 29x95x80 | 151 | C005 | C014 |
| 5 | 36x47 | 29x102x80 | 160 | C006 | C015 |
| 6 | 22x57 | 29x100x90 | 180 | C007 | C016 |
| 6 | 29x57 | 29x107x90 | 186 | C008 | C017 |
| 6 | 36x57 | 29x114x90 | 199 | C009 | C018 |



One Piece Mini Crossovers

A great solution to navigate over low running pipes, electrical conduits or other permanent objects. Strong all welded construction made of heavy gauge rectangular tubing. Steps and platforms are made of durable grip strut. Two step models have a 60 degree incline angle. Weight capacity 500 lbs.

MINICO-9.5



MINICO-19-AL



| Material | EGA # | # of Steps | Clearance WxH | Overall WxLxH | Weight |
|----------|---------------|------------|------------------|------------------|--------|
| Steel | MINICO-9.5 | 1 | 25x6½ | 26½x39¾x9½ | 31 |
| Steel | MINICO-19 | 2 | 25x16 | 26½x51x19 | 52 |
| Aluminum | MINICO-9.5-AL | 1 | 25x6½ | 26½x39¾x9½ | 14 |
| Aluminum | MINICO-19-AL | 2 | 25x16 | 26½x51x19 | 24 |